

## GS-3384 RT SCISSOR LIFT

### 33FT DIESEL SCISSOR LIFT ROUGH TERRAIN

MODEL	GS™-3384 RT	
MEASUREMENTS	Metric	US
Working height maximum*	12.06 m	39 ft
<b>A</b> Platform height maximum	10.06 m	33 ft
<b>B</b> Platform height - stowed**	1.55 m	5 ft 1 in
<b>C</b> Platform length:	3.98 m	13 ft 0.5 in
outside, extended - single deck	5.34 m	17 ft 6.25 in
outside, extended - dual deck	6.57 m	21 ft 6.5 in
<b>D</b> Slide-out platform extension deck - front	1.52 m	5 ft
<b>E</b> Slide-out platform extension deck - rear	1.22 m	4 ft
<b>F</b> Platform width - outside	1.83 m	6 ft
<b>G</b> Height - stowed: - folding guardrails	2.68 m	8 ft 9.5 in
- rails lowered	2.00 m	6 ft 6.75 in
<b>H</b> Length - stowed with outriggers	4.88 m	16 ft
<b>I</b> Width: - standard tyres	2.13 m	7 ft
- high flotation tyres	2.41 m	7 ft 11 in
<b>J</b> Wheelbase	2.84 m	9 ft 4 in
<b>K</b> Ground clearance - centre	0.33 m	13 in

PRODUCTIVITY		
Maximum platform occupancy	7	7
Lift capacity	1,134 kg	2,500 lbs
Lift capacity - extension deck	227 kg	500 lbs
Drive speed - stowed	6.4 km/h	4.0 mph
Drive speed - raised	1.1 km/h	0.7 mph
Gradeability - stowed***	50%	50%
Maximum outrigger leveling: - front to back	7°	7°
- side to side	12°	12°
Turning radius - inside	3.09 m	10 ft 1.5 in
Turning radius - outside	5.94 m	19 ft 6 in
Raise/lower speed	45 / 29 sec	45 / 29 sec
Controls	proportional	
Drive	four wheel	
Tyres - foam-filled rough terrain	25 x 79 cm	10 x 31 in

POWER		
Power source	Deutz D2011L03i 3 cylinder diesel	
	36 kW (49 hp) air cooled	
Auxiliary Power unit	12V DC	
Fuel tank capacity	113.6 L	30 gal
Hydraulic system capacity	113.6 L	30 gal

WEIGHT****		
with outriggers	6,743 kg	14,866 lbs

**STANDARDS COMPLIANCE** ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
 \*\* Based on RT tyres. Deduct 2 in (5.8 cm) for turf and non-marking.  
 \*\*\* Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.  
 \*\*\*\* Weight will vary depending on options and/or country standards.

