

S1008-ACE+ SCISSOR LIFT

32FT ELECTRIC SCISSOR LIFT NARROW

Dimension	Metric	British
Max. Working Height A	12.00m	39ft 4in
Max. Platform Height B	10.00m	32ft 10in
Overall Length C	2.48m	8ft 2in
Overall Width D	0.83m	2ft 9in
Overall Height(Rails Up) E	2.51m	8ft 3in
Overall Height(Rails Down) F	2.05m	6ft 9in
Platform Size(Length x Width)	2.27m x 0.81m	7ft 5in x 2ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.10m	0in/6ft 11in
Tyres	φ381 x 127mm	φ381 x 127mm

Performance		
S.W.L	250kg	551lb
S.W.L on Extension	113kg	249lb
Max. Occupants (Indoor/Outdoor)	2/1	2/1
Gradeability	25%	25%
Travel Speed(Stowed)	5.0km/h	3.10mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	51/42sec	51/42sec

Weight		
Overall Weight	3150kg	6944lb

Power		
Hydraulic Tank	20L	5.3gal
Battery	24V/240Ah	24V/240Ah
Charger	24V/30A	24V/30A
Driving Motor	2 x 15VAC/0.87kW	2 x 15VAC/0.87kW
Lifting Motor	16VAC/3.5kW	16VAC/3.5kW

