MOBILE AC SERIES MAC5K-10



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.











PRODUCT SPECIFICATIONS

GENERAL

Model Voltage **Output Power** Frequency

MAC 5k-10-VS

BATTERY

Battery Type **Battery Voltage** AC Output Capacity **Recharge Time** Fast Charge

CATL- Lithium Iron Phosphate
48V DC
8.3kWh
3 hours (10-100%)
50% battery capacity in 1 hour (SOC between 10-80%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C (derates above 25°C)
Altitude	0 - 1500m (>1500m derating)
IP Rating	IP54
Input	15A 3 pin plug - IP66 with 5m lead
Output	15A 3 pin GPO - IP66
SOLAR INPUT	
Solar Input	4kWp max. 250v max.
Generator	Remote Start feature
UNIT	
Dimensions (HxWxD)	1000 x 700 x 700
Weight	180 kg