


Globe Power's lithium ion Hybrid AC units provide a reduction of diesel consumption and are low emission assisting in reducing carbon footprint and hitting green energy emission targets.

Suitable for a high load start up and low running power demands, the all in one system is both efficient in power and cost.



Powered By:



PRODUCT SPECIFICATIONS

GENERAL

Model	HAC20K-20
Voltage	230V AC 50Hz
Output Power	15kVA continuous load, Peak 30kVA

BATTERY

Battery Type	Lithium Iron Phosphate
Battery Voltage	48V DC
AC Output Capacity	16.6kWh
Recharge Time	3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C (derates above 35°C)
Altitude	0 - 1500m (>1500m derating)
IP Rating	IP54
Output	10A, 15A, 32A, 63A, ip66 outlets
Fuel	60L Tank

UNIT

Dimensions (LxWxH)	1650 x 704 x 2073
Weight ATS	1200 kg

FUEL CONSUMPTION

Fuel Consumption* (L/h)	1.9
<small>*Based on 75% load</small>	
Fuel Tank Capacity (L)	60

NOISE LEVEL

Sound Pressure	68db @ 7m
----------------	-----------

SOLAR

Voltage	250v DC Max
Power	2 x 4kW Charge Controllers