MOBILE AC SERIES MAC15K3-30



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.













PRODUCT SPECIFICATIONS

GENERAL

Model Voltage Output Power Frequency

MAC 15k3-30 400v AC 3 phase 15kVA @ 25°C, 12.2kVA @ 40°C 50Hz

BATTERY

Battery Type Battery Voltage AC Output Capacity Recharge Time Solartech- Lithium Iron Phosphate 48V DC 25kWh 3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C (derates above 25°C)
Altitude	0 - 1500m (>1500m derating)
IP Rating	IP54
Input	32A 3/5 pin plug - IP66
Output	32A 3 pin Outlet - IP66
SOLAR INPUT	
Solar Input	4kWp max. 250v max (Optional 12kWp)
Generator	Remote Start Feature
UNIT	
Dimensions (HxWxD)	1780 x 1350 x 710
Weight	950kg

GLOBEPOWER.NET